

INDUSTRIAL COMPONENT DATA

CSD-SL 300 WH 30X30 1051096 PHOENIX CONTACT Signal lamp

Brand: PHOENIX CONTACT | Manufacturer Part Number: CSD-SL 300 WH 30X30



Manufacturer	PHOENIX CONTACT
MPN / Reference	CSD-SL 300 WH 30X30
Catalog number	1051096
Category	Monitored LED indicator luminaire
Minimum order	1 Pcs
Document ID	EO-700A98E076
Generated	2026-08-05

Product Overview

Signal lamp

Signal light with an emission angle of 30 x 30 total angle, 24 V DC, white, communication

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data

Orderkey 1051096

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626669595

Weight per Piece (excluding packing) 3,860.000 g

Custom tariff number 85308000

Country of origin DE (Germany)

Dimensions

Width 272 mm

Height 291 mm

Depth 68 mm

Length 272 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C
Ambient temperature (storage/transport) -25 °C ... 85 °C
Air pressure (operation) 70 hPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport) 70 hPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection IP65/IP67, when installed
General
Assembly instructions Use of stainless steel fittings (corrosion-resistant)
Net weight 3860 g
Diagnostics messages LEDs; temperature, current, voltage, etc. Yes
Mains failure, communication failure Failsafe
Design Operating hours counter
Inrush current max. 36 A ()
Power supply for module electronics
Connection method M17 hybrid connectors with SPEEDCON locking system
Number of positions 8
Supply voltage 24 V DC (DC)
Current consumption max. 2.51 A (white LEDs)
Power consumption max. 70 W (white LEDs)
Light properties
Source of light type LED
Number of LEDs 30 (according to IALA recommendation E200-1 and CIE 1931)
Service life, lighting appliance 50000 h
Light color IALA white, optimum
Color temperature / wavelength 5000 K $\pm$ 1000K
Color class C3 (EN 12966)
Luminance L3 (EN 12966)
Luminance ratio R3 (EN 12966)
Phantom light class 5 (EN 12368)
Luminous intensity 12706...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CSD-SL 300 WH 30X30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.