

## INDUSTRIAL COMPONENT DATA

# CSS 0.75-1/3 1201509 PHOENIX CONTACT Speed starter with soft start and adjustable speed for starting and rev..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CSS 0.75-1/3



|                 |                  |
|-----------------|------------------|
| Manufacturer    | PHOENIX CONTACT  |
| MPN / Reference | CSS 0.75-1/3     |
| Catalog number  | 1201509          |
| Category        | Speed controller |
| Minimum order   | 1 Pcs            |
| Document ID     | EO-5D8EB7C698    |
| Generated       | 2026-08-04       |

## Product Overview

Speed starter with soft start and adjustable speed for starting and reversing motors up to 230 V AC and 0.75 kW, adjustable motor protection, analog input, STO function up to SIL 3 / PL e, single-phase load input

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; INTERFACE Components (IF)

## Additional Product Information

Technical dataItem PropertiesProduct Type Speed Starters

Product Family CONTACTRON

Operation Elements Button

Rotary switch

Insulation Properties

Degree of pollution 2

Electrical PropertiesNumber of phases 1

Input dataNet

Number of phases 1

Input voltage 230 V AC

240 V AC

Input Voltage Range 110 V AC ... 240 V AC -15% ... +10%

Frequency Range 47 Hz ... 63 Hz

Nominal current 9.1 A (without mains inductance)

8.3 A (with mains inductance)  
Output DataNominal motor power 0.75 kW  
Apparent power 1.7 kVA  
Rated Output Current (IN) 4.3 A (4 kHz)  
3.5 A (8 kHz)  
2.4 A (16 kHz)  
Output Frequency 0 Hz ... 500 Hz  
Dissipated Power 37 W (2 kHz)  
42 W (4 kHz)  
40 W (8 kHz)  
38 W (16 kHz)  
9 W (Stand-By)  
Output current  $\leq 6.45$  A (180 sec)  
 $\leq 3.225$  A (180 s, during recovery time)  
 $\leq 7.74$  A (15 sec)  
 $\leq 2.15$  A (15 s, during recovery time)  
Recovery Time 150 s (180 sec)  
12 s (15 s)  
Overload Time 30 sec (180 sec)  
3 s (15 s)  
Discharge Time 3 min. (Intermediate Circuit Capacitors)  
Commute  
Denomination Output Relay Output  
Contact Switching Type 1 switch  
Maximum Switching Voltage 125 V AC  
30 V DC  
Maximum connection current 3 A  
Minimum Shut-Off Current 10 mA (5 V DC)  
Connection dataAWG Conductor Section (Converted according to IEC)  
Power terminals  
Connection type Push-in connection  
Length to be de-insulated 10 mm  
Rigid conductor section 0.2 mm<sup>2</sup> ... 6 mm<sup>2</sup>  
Flexible conductor section 0.2 mm<sup>2</sup> ... 6 mm<sup>2</sup>  
0.2 mm<sup>2</sup> ... 4 mm<sup>2</sup> (with toe cap)  
AWG Conductor Section 24 ... 10  
Control Modules  
Connection type Push-in connection  
Le...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CSS 0.75-1/3 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.