

INDUSTRIAL COMPONENT DATA

CUC-DSI-J1STZ-S/DSL SB25 HD 1418738 PHOENIX CONTACT D-SUB contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: CUC-DSI-J1STZ-S/DSL SB25 HD



Manufacturer	PHOENIX CONTACT
MPN / Reference	CUC-DSI-J1STZ-S/DSL SB25 HD
Catalog number	1418738
Category	D-Sub connector
Minimum order	10 Pcs
Document ID	EO-D6FC6F1373
Generated	2026-08-06

Product Overview

D-SUB contact insert

D-SUB contact insert, protection index: IP20, number of poles: 44, material: Steel, connection type: Welding pins

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1418738

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4055626150048

Weight per Piece (excluding packing) 2.220 g

Custom tariff number 85366990

Country of origin TW (Taiwan)

Mechanical characteristics

Standards/specifications DIN 41652

Number of positions 44

Number of slots 1

Connection profile 25-pos. D-SUB

Insertion/withdrawal cycles 50

Connection method Solder pins

Type of contact punched contacts

Mounting type 4-40 UNC thread

Type 25

Ambient conditions

Ambient temperature (operation) -55 °C ... 105 °C

Material data

Flammability rating according to UL 94 V0

Housing material Steel

Housing surface material tin-plated

Contact carrier material Glass-fiber reinforced thermoplastics, UL 94 V0

Contact material Copper alloy

Contact surface material Sn/Au

Electrical characteristics

Number of positions 44

Rated current 3 A

Degree of pollution 2

Test voltage 1000 V AC

Standards and Regulations

Standards/regulations DIN 41652

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440302eCl@ss 8.027440302eCl@ss 9.027440302

ETIM 2.0EC000438ETIM 3.0EC000438ETIM 4.0EC000438ETIM 5.0EC001132ETIM 6.0EC001132

UNSPSC 6.0130211923UNSPSC 7.090139121522UNSPSC 1139121522UNSPSC 12...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CUC-DSI-J1STZ-S/DSLSEB25 HD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.