

## INDUSTRIAL COMPONENT DATA

# CUC-DST-GZNI-A/DSSC25 1419728 PHOENIX CONTACT D-SUB sleeve housings

Brand: PHOENIX CONTACT | Manufacturer Part Number: CUC-DST-GZNI-A/DSSC25



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | PHOENIX CONTACT                    |
| MPN / Reference | CUC-DST-GZNI-A/DSSC25              |
| Catalog number  | 1419728                            |
| Category        | Housing for rectangular connectors |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-E0F7B3D55F                      |
| Generated       | 2026-08-06                         |

## Product Overview

D-SUB sleeve housings

D-SUB bobbin housing, protection index: IP20, material: Zinc injected casting, cable outlet: elbowed, housing size: 3, color: Metallic, bare

D-SUB sleeve housings, degree of protection: IP20, material: Zinc die-cast, cable outlet: angled, housing size: 3, color: Bare metallic

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

## Additional Product Information

Technical dataProduct propertiesProduct type Sleeve housings

Type D-SUB

No. of cable outlets 1

Cable outlet angled

Data management status

Article revision 00

Connection dataScrew thread 4-40 UNC

DimensionsWidth 53.7 mm

Height 15.2 mm

Depth 61.3 mm

Material specificationsColor Bare metallic

Flammability rating according to UL 94 V0  
Housing material Zinc die-cast  
Housing surface material nickel-plated  
Cable/line External cable diameter 3 mm ... 8.5 mm (Without bending protection)  
Environmental and real-life conditions Ambient conditions  
Degree of protection IP20  
Ambient temperature (operation) -35 °C ... 100 °C  
Mounting Mounting type Screw locking mechanism  
ETIM for 1419728 Connectors (EC000437)  
Feature Name  
Feature Value  
Width (EF000008)  
53.7 mm  
Height (EF000040)  
15.2 mm  
Housing material (EF001596)  
Other  
Coating housing (EF001601)  
Other  
With cable screw gland (EF000735)  
No  
Mounting method of the cable gland (EF012210)  
Other  
With hinged lid (EF000117)  
No  
With distance piece (EF005072)  
No  
With sealing (EF005610)  
No  
Number of conduit inlets (EF000437)  
1  
Operating temperature (EF002393)  
-35 °C  
EMC-version (EF001062)  
Yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CUC-DST-GZNI-A/DSSC25 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.