


INDUSTRIAL COMPONENT DATA

CUC-DST-GZNI-S/DSSC25 1419727 PHOENIX CONTACT D-SUB sleeve housings

Brand: PHOENIX CONTACT | Manufacturer Part Number: CUC-DST-GZNI-S/DSSC25



Manufacturer	PHOENIX CONTACT
MPN / Reference	CUC-DST-GZNI-S/DSSC25
Catalog number	1419727
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-F55FCC1EB5
Generated	2026-08-06

Product Overview

D-SUB sleeve housings

D-SUB bobbin housing, protection index: IP20, material: Zinc injected casting, cable outlet: straight, housing size: 3, color: Metallic, bare

D-SUB cover, protection class: IP20, material: Zinc die-casting, cable outlet: straight, housing size: 3, colour: metallic white

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1419727

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626188058

Weight per Piece (excluding packing) 72.450 g

Custom tariff number 85389099

Country of origin DE (Germany)

Mechanical characteristics

External cable diameter 3 mm ... 8.5 mm (Without bending protection)

Cable outlet straight

Color Bare metallic

Mounting type Screw locking

Screw thread 4-40 UNC

Degree of protection IP20

Type D-SUB 25

Size of housing 3

No. of cable outlets 1

Ambient conditions

Ambient temperature (operation) -35 °C ... 100 °C

Material data

Flammability rating according to UL 94 V0

Housing material Zinc die-cast

Housing surface material Nickel-plated

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss

7.027440302eCl@ss 8.027440302eCl@ss 9.027440302

ETIM 2.0EC000437ETIM 3.0EC000437ETIM 4.0EC000437ETIM 5.0EC001132ETIM 6.0EC001132

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC

13.239121522

ETIM for 1419727 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

53.7 mm

Height (EF000040)

15.2 mm

Housing material (EF001596)

Other

Coating housing (EF001601)

Other

Position cable feed (EF008218)

Other

With cable screw gland (EF000735)

No

Mounti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CUC-DST-GZNI-S/DSSC25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.