

INDUSTRIAL COMPONENT DATA

CUC-I-D1ZNI-S/R4GC8 1041760 PHOENIX CONTACT RJ45 coupling, degree of protection: IP20, number of positions: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CUC-I-D1ZNI-S/R4GC8



Manufacturer	PHOENIX CONTACT
MPN / Reference	CUC-I-D1ZNI-S/R4GC8
Catalog number	1041760
Category	Fibre optic attenuator
Minimum order	1 Pcs
Document ID	EO-C43EBFE56E
Generated	2026-08-06

Product Overview

RJ45 coupling, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6

RJ45 coupling, protection index: IP20, number of poles: 8, 10 GBit/s, CAT6A, material: Metal, connection type: 2x RJ45, version without adapter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1041760

Packing unit 1 pc

Catalog page Page 375 (C-2-2019)

GTIN 4055626599915

Weight per Piece (excluding packing) 20.000 g

Custom tariff number 85366990

Country of origin PL (Poland)

Drawings

Ambient conditions

Electrical characteristics

Environmental Product Compliance

Mechanical characteristics

[Material data](#)[Standards and Regulations](#)[Classifications](#)[Drawings](#)[Dimensional drawing](#)[Back to top](#)[Mechanical characteristics](#)[Connection method 2x RJ45](#)[Number of slots 2](#)[Transmission speed 10 Gbps](#)[Transmission characteristics \(category\) CAT6A](#)[Back to top](#)[Ambient conditions](#)[Ambient temperature \(operation\) -10 °C ... 60 °C](#)[Degree of protection IP20](#)[Back to top](#)[Material data](#)[Contact surface material Gold over nickel](#)[Contact material Spring steel](#)[Housing material Zinc die-cast](#)[Housing surface material metal-plated](#)[Back to top](#)[Electrical characteristics](#)[Number of positions 8](#)[GRP transmission properties CAT6A in accordance with ISO/IEC 11801](#)[Transmission speed 10 Gbps](#)[Frequency range 500 MHz](#)[Dielectric strength > 1000 V DC](#)[Contact resistance 200 mΩ \(Trunk in to trunk out\)](#)[Rated voltage \(III/3\) 72 V \(DC\)](#)[Back to top](#)[Standards and Regulations](#)[Standards/specifications IEC 60603-7 DIN EN 50173-1 ISO/IEC 11801-Am.1 IEC 60068-2](#)[Back to top](#)[Environmental Product Compliance](#)[China RoHS Environmentally friendly use period: unlimited = EFUP-e](#)[No hazardous substances above threshold values](#)[Back to top](#)[Classifications](#)[eCl@ss](#)[eCl@ss 10.0.1 19179290](#)[eCl@ss 9.0 19179290](#)[Back to top](#)[ETI...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CUC-I-D1ZNI-S/R4GC8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.