

INDUSTRIAL COMPONENT DATA

CUC-PP-FR19:1U-I-EMPTY:24 1422978 PHOENIX CONTACT

Marshalling panel

Brand: PHOENIX CONTACT | Manufacturer Part Number: CUC-PP-FR19:1U-I-EMPTY:24



Manufacturer	PHOENIX CONTACT
MPN / Reference	CUC-PP-FR19:1U-I-EMPTY:24
Catalog number	1422978
Category	Accessories/spare parts for firewall appliances
Minimum order	1 Pcs
Document ID	EO-B06FAEDF0F
Generated	2026-07-29

Product Overview

Marshalling panel

Patch panel, 19" mounting, IP20, with 24 mounting spaces optionally for RJ45 cable patch modules, RJ45 coupler modules, LC-Duplex, SC-Simplex and MPO, medium gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1422978

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 395 (C-2-2017)

GTIN 4055626319926

Weight per Piece (excluding packing) 808.000 g

Custom tariff number 85389099

Country of origin CN (China)

Mechanical characteristics

Number of slots 24

Connection profile RJ45

Connection method Quick connection

Color gray

Mounting type 19" rack

Insulation resistance according to IEC 61010-1

Degree of protection IP20

Size of housing 1

No. of cable outlets 24

Ambient conditions

Ambient temperature (operation) 5 °C ... 55 °C

Ambient temperature (assembly) -25 °C ... 55 °C

Ambient temperature (storage/transport) -5 °C ... 55 °C

Degree of protection IP20

Material data

Flammability rating according to UL 94 V0

Housing material PC-GF

Material Steel, galvanized

Depth 83.4 mm

Height 43.6 mm

Standards and Regulations

Flammability rating according to UL 94 V0

Shock Acceleration time 30 m/s² in all 6 directions

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 6.027261200eCl@ss 7.027440210eCl@ss 8.027440210eCl@ss 9.027440210

ETIM 6.0EC002310

ETIM for 1422978 Connectors (EC002310)

Feature Name

Feature Value

Material assembly frame (EF007542)

Other

With PE-connection (EF005600)

No

Inflammability class of insulation material according to UL94 (EF002521)

V0

Fixing direction (EF012208)

Swivelling...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CUC-PP-FR19:1U-I-EMPTY:24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.