

INDUSTRIAL COMPONENT DATA

CUC-V06-C1PBK-S/R4CE8:1 1414408 PHOENIX CONTACT RJ45 connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: CUC-V06-C1PBK-S/R4CE8:1



Manufacturer	PHOENIX CONTACT
MPN / Reference	CUC-V06-C1PBK-S/R4CE8:1
Catalog number	1414408
Category	Fibre optic attenuator
Minimum order	1 Pcs
Document ID	EO-09CE193965
Generated	2026-08-06

Product Overview

RJ45 connector

RJ45 plug-in connector, construction: RJ45, protection index: IP67, number of poles: 8, 1 GBit/s, CAT6, material: PA, connection type: Crimped connection, connection section: AWG 24- 27, cable output: straight, color: black, Ethernet / PROFINET

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1414408

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 354 (C-2-2017)

GTIN 4055626028309

Weight per Piece (excluding packing) 19.700 g

Custom tariff number 85389099

Country of origin DE (Germany)

Mechanical characteristics

Number of positions 8

Connection profile RJ45

Insertion/withdrawal cycles ≥ 750
Connection method Crimp connection
Type of contact Crimp contacts
Conductor cross section $0.1 \text{ mm}^2 \dots 0.2 \text{ mm}^2$ (flexible)
Connection cross section AWG 24 ... 27 (flexible)
External cable diameter 5 mm ... 8.5 mm
Cable outlet straight
Color black
Degree of protection IP67
Type RJ45, IP67, version 6
No. of cable outlets 1
Ambient conditions
Ambient temperature (operation) $-25 \text{ }^{\circ}\text{C} \dots 60 \text{ }^{\circ}\text{C}$
Material data
Flammability rating according to UL 94 V0
Housing material PA
Contact carrier material PC
Contact material Phosphor bronze
Contact surface material Gold
O-ring material FPM
Cable seal material NBR
Electrical characteristics
Number of positions 8
Nominal voltage UN 72 V (DC)
Nominal current IN 1.75 A
Transmission characteristics (category) CAT6
GRP transmission properties CAT6 CAT6
Transmission speed 1 Gbps (250 MHz)
Frequency range to 250 MHz
Rated current 1 A
Overvoltage category I
Degree of pollution 2
Rated voltage (III/3) 72 V (DC)
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CUC-V06-C1PBK-S/R4CE8:1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.