

INDUSTRIAL COMPONENT DATA

D-ST 2,5-QUATTRO BU 1072361 PHOENIX CONTACT End cover, length: 72,2 mm, width: 2.2 mm, height: 29,1 mm, colo..

Brand: PHOENIX CONTACT | Manufacturer Part Number: D-ST 2,5-QUATTRO BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	D-ST 2,5-QUATTRO BU
Catalog number	1072361
Category	Endplate and partition plate for terminal block
Minimum order	50 Pcs
Document ID	EO-02F635B2DE
Generated	2026-08-05

Product Overview

End cover, length: 72,2 mm, width: 2.2 mm, height: 29,1 mm, color: blue

End cover, depth: 29.1 mm, width: 2.2 mm, height: 72.2 mm, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type End cover

Data management status

Article revision 00

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (operation) 20 % ... 90 %

Permissible humidity (storage/transport) 30 % ... 70 %

Material specificationsColor blue (RAL 5015)

Material PA

Flammability rating according to UL 94 V0

Static insulating material application in cold -60 °C
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
DimensionsWidth 2.2 mm
Height 72.2 mm
Depth 29.1 mm
ETIM for 1072361 Terminal blocks (EC000886)
Feature Name
Feature Value
Colour (EF000007)
Blue
Thickness (EF000125)
2.2 mm
Inflammability class of insulation material accordi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / D-ST 2,5-QUATTRO BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.