

INDUSTRIAL COMPONENT DATA

VS-09-PROFIBUS-SC 1654549 PHOENIX CONTACT D-SUB connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-09-PROFIBUS-SC



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-09-PROFIBUS-SC
Catalog number	1654549
Category	Accessories/spare parts for industrial connectors
Minimum order	1 Pcs
Document ID	EO-6187ED169C
Generated	2026-08-02

Product Overview

D-SUB connector

D-SUB plug-in connector, protection index: IP67, number of poles: 9, material: PA, connection type: Screw connection, connection section: AWG 26- 16, cable output: inclined, with integrated closing resistance, housing size: 1, color: gray, PROFIBUS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1654549

Packing unit 1 pc

Catalog page Page 444 (C-2-2017)

GTIN 4017918955083

Weight per Piece (excluding packing) 93.500 g

Custom tariff number 85366990

Country of origin DE (Germany)

Mechanical characteristics

Number of positions 9

Shielded yes

Insertion/withdrawal cycles >= 200

Connection method Screw connection

Conductor cross section 0.14 mm² ... 1.5 mm² (solid)

0.14 mm² ... 1 mm² (flexible)

Connection cross section AWG 26 ... 16 (solid)

26 ... 18 (flexible)

External cable diameter 5 mm ... 9 mm

Cable outlet Angled

Color gray

Degree of protection IP67

Type D-SUB 9

Size of housing 1

No. of cable outlets 2

Ambient conditions

Ambient temperature (operation) -20 °C ... 75 °C

Degree of protection IP67

Material data

Flammability rating according to UL 94 V0

Housing material PA

Housing surface material PA, light gray

Cable seal material CR/NBR

Height 59 mm

Electrical characteristics

Number of positions 9

Rated current 1 A

Overvoltage category II

Degree of pollution 2

Rated voltage (III/3) 50 V

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440302eCl@ss 8.027440302eCl@ss 9.027440302

ETIM 2.0EC001121ETIM 3.0EC001132ETIM 4.0EC002641ET...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-09-PROFIBUS-SC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.