

INDUSTRIAL COMPONENT DATA

SUBCON-PLUS 9/M 2744018 PHOENIX CONTACT D-SUB bus connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SUBCON-PLUS 9/M



Manufacturer	PHOENIX CONTACT
MPN / Reference	SUBCON-PLUS 9/M
Catalog number	2744018
Category	D-Sub connector
Minimum order	1 Pcs
Document ID	EO-B80F4F1168
Generated	2026-08-01

Product Overview

D-SUB bus connector

D-SUB connector, 9 poles, male connector, two cable entries under 35°, universal model for all systems, pin occupancy: 1, 2, 3, 4, 5, 6, 7, 8, 9 on a screw connection terminal respectively

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 2744018

Packing unit 1 pc

Catalog page Page 378 (C-6-2017)

GTIN 4017918888817

Weight per Piece (excluding packing) 73.400 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Max. cable diameter 10 mm

Min. cable diameter 6 mm

Width 16 mm

Height 44 mm

Length 60 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 75 °C

Ambient temperature (storage/transport) -25 °C ... 80 °C

Altitude 5000 m (For restrictions see manufacturer's declaration)

Degree of protection IP20

General

Nominal voltage UN 50 V DC

Nominal current IN 100 mA

Bus system RS-485

Signal RS-485

Insertion/withdrawal cycles > 200

SUBCON fixing screws 4-40 UNC

Tightening torque 0.4 Nm

Housing material ABS, metal-plated

Pin assignment all 1:1

MTTF 6706 Years (SN 29500 standard, temperature 25 °C, operating cycle 21 % (5 days a week, 8 hours a day))

1817 Years (SN 29500 standard, temperature 40 °C, operating cycle 34.25 % (5 days a week, 12 hours a day))

155 Years (SN 29500 standard, temperature 40 °C, operating cycle 100 % (7 days a week, 24 hours a day))

Connection data

Connection D-SUB connection

Number of positions 9

Connection method D-SUB connector

Tightening torque 0.4 Nm

Connection PCB connection

Connection method Screw connection

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1 mm²

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Min. AWG conductor cross section, flexible 26...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SUBCON-PLUS 9/M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.