

INDUSTRIAL COMPONENT DATA

VS-09-ST-DSUB-2P-LH 1655292 PHOENIX CONTACT D-SUB contact support

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-09-ST-DSUB-2P-LH



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-09-ST-DSUB-2P-LH
Catalog number	1655292
Category	D-Sub connector
Minimum order	100 Pcs
Document ID	EO-C68D699049
Generated	2026-08-02

Product Overview

D-SUB contact support

D-SUB contact holder, wrap size 1, housing for 2 combined contacts, male contact type, fastening by 4-40 UNC thread and welding pins, for VS-09 recessed frame-...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

Key Commercial Data

Orderkey 1655292

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 214 (C-2-2013)

GTIN 4046356029230

Weight per Piece (excluding packing) 10.310 g

Custom tariff number 85366990

Country of origin DE (Germany)

Mechanical characteristics

Number of positions 2

Insertion/withdrawal cycles >= 500

Connection method Fitting to accept combined contact

Type of contact Pin

Mounting type Threads and solder pins

Type D-SUB 9

Size of housing 1

Type of note Order information:

Note The contacts must be ordered separately since they are not included in the scope of supply of the contact carriers.

Both one male and one female contact must be mounted in the contact carrier.

Ambient conditions

Ambient temperature (operation) -55 °C ... 125 °C

Material data

Flammability rating according to UL 94 V0

Housing material Steel, yellow chromated

Contact carrier material PBTP

Contact surface material Gold over nickel

Electrical characteristics

Number of positions 2

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440302eCl@ss 8.027440302eCl@ss 9.027440205

ETIM 2.0EC000438ETIM 3.0EC000438ETIM....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-09-ST-DSUB-2P-LH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.