

## INDUSTRIAL COMPONENT DATA

# VS-25-ST-DSUB-5P 1689970 PHOENIX CONTACT D-SUB contact support

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-25-ST-DSUB-5P



|                 |                  |
|-----------------|------------------|
| Manufacturer    | PHOENIX CONTACT  |
| MPN / Reference | VS-25-ST-DSUB-5P |
| Catalog number  | 1689970          |
| Category        | D-Sub connector  |
| Minimum order   | 100 Pcs          |
| Document ID     | EO-94318D7E5C    |
| Generated       | 2026-08-04       |

## Product Overview

D-SUB contact support

D-SUB contact holder, wrap size 3, housing for 5 combined contacts, male contact type, straight, fixing by drill 3 mm, for recessed frame and VS-25 overhead housing-...

D-SUB contact holder, wrap size 3, housing for 5 combined contacts, contact connection type: male, straight, fixing by 3 mm hole, for recessed frame and VS-25 aerial housing-...

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Field Device Connectors (FDC)

## Additional Product Information

Key Commercial Data

Orderkey 1689970

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 214 (C-2-2013)

GTIN 4017918914370

Weight per Piece (excluding packing) 7.590 g

Custom tariff number 85366990

Country of origin DE (Germany)

Mechanical characteristics

Number of positions 5

Insertion/withdrawal cycles  $\geq 500$

Connection method Fitting to accept combined contact

Mounting type Hole

Type D-SUB 25

Size of housing 3

Type of note Order information:

Note The contacts must be ordered separately since they are not included in the scope of supply of the contact carriers.

Ambient conditions

Ambient temperature (operation)  $-55\text{ }^{\circ}\text{C} \dots 125\text{ }^{\circ}\text{C}$

Material data

Flammability rating according to UL 94 V0

Housing material Steel, yellow chromated

Contact carrier material PBTP

Contact surface material Gold over nickel

Electrical characteristics

Number of positions 5

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss  
7.027440302eCl@ss 8.027440302eCl@ss 9.027440205

ETIM 2.0EC000437ETIM 3.0EC000437ETIM 4.0EC000438ETIM 5.0EC001132ETIM 6.0EC000438

UNSPSC 6.0130211923UNSPSC 7.090139121522UNSPSC 1139121522UNSPSC 12.0139121522UNSPSC  
13.239121522

ETIM for 1689970 Connectors (EC003557)....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-25-ST-DSUB-5P with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.