

INDUSTRIAL COMPONENT DATA

VS-25-ST-DSUB-5P-LH 1655441 PHOENIX CONTACT D-SUB contact support

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-25-ST-DSUB-5P-LH



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-25-ST-DSUB-5P-LH
Catalog number	1655441
Category	D-Sub connector
Minimum order	100 Pcs
Document ID	EO-7F3E4435FD
Generated	2026-08-02

Product Overview

D-SUB contact support

D-SUB contact holder, wrap size 3, housing for 5 combined contacts, male contact type, fastening by 4-40 UNC thread and welding pins, for VS-25 recessed frame-...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1655441

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 214 (C-2-2013)

GTIN 4046356029377

Weight per Piece (excluding packing) 13.030 g

Custom tariff number 85366990

Country of origin DE (Germany)

Mechanical characteristics

Number of positions 5

Insertion/withdrawal cycles >= 500

Connection method Fitting to accept combined contact

Type of contact Pin

Mounting type Threads and solder pins

Type D-SUB 25

Size of housing 3

Type of note Order information:

Note The contacts must be ordered separately since they are not included in the scope of supply of the combi contact inserts.

Ambient conditions

Ambient temperature (operation) -55 °C ... 125 °C

Material data

Flammability rating according to UL 94 V0

Housing material Steel, yellow chromated

Contact carrier material PBTP

Contact surface material Gold over nickel

Electrical characteristics

Number of positions 5

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440302eCl@ss 8.027440302eCl@ss 9.027440205

ETIM 2.0EC000438ETIM 3.0EC000438ETIM 4.0EC000438ETIM 5.0EC001132ETIM 6.0EC000438

UNSPSC 6.0130211923UNSPSC 7...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-25-ST-DSUB-5P-LH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.