

## INDUSTRIAL COMPONENT DATA

## VS-09-GC-BU/BU 1688722 PHOENIX CONTACT D-SUB gender changer

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-09-GC-BU/BU



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | PHOENIX CONTACT |
| MPN / Reference | VS-09-GC-BU/BU  |
| Catalog number  | 1688722         |
| Category        | D-Sub connector |
| Minimum order   | 10 Pcs          |
| Document ID     | EO-5FF794F863   |
| Generated       | 2026-07-29      |

## Product Overview

D-SUB gender changer

D-SUB contact insert, wrap size 1, with 9 signal contacts, female contact type, Gender-Changer, 4-40 UNC thread attachment

D-SUB gender changer, degree of protection: IP20, number of positions: 9, material: Metal, connection method: Coupling, cable outlet: angled, housing size: 1, Universal

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

## Additional Product Information

Technical dataProduct propertiesProduct type Data connector (cable side)

Type D-SUB

Sensor type Universal

Number of positions 9

Type Female/Female

Shielded no

Cable outlet angled

Data management status

Article revision 02

Insulation characteristics

Overvoltage category III

Degree of pollution 2  
Electrical properties Rated voltage (III/3) 125 V  
Rated surge voltage 1 kV  
Rated current 5 A  
Transmission medium Copper  
Connection data Connection technology  
Connection method Coupling  
Dimensions Width 17.6 mm  
Height 30.86 mm  
Length 12.5 mm  
Material specifications Flammability rating according to UL 94 V0  
Housing material Metal  
Contact material Copper alloy  
Contact surface material Hard gold-plated over nickel  
Contact carrier material Polyester GF  
Mechanical properties Mechanical data  
Insertion/withdrawal cycles  $\geq 200$   
Environmental and real-life conditions Ambient conditions  
Degree of protection IP20  
Ambient temperature (operation) -55 °C ... 125 °C  
Mounting Mounting type Threads  
ETIM for 1688722 Connectors (EC003557)  
Feature Name  
Feature Value  
Number of poles (EF001391)  
9

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-09-GC-BU/BU with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.