

INDUSTRIAL COMPONENT DATA

VS-25-BU-DSUB-4P-5S 1655373 PHOENIX CONTACT D-SUB combination contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-25-BU-DSUB-4P-5S



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-25-BU-DSUB-4P-5S
Catalog number	1655373
Category	Contact insert for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-5FC88D4023
Generated	2026-07-29

Product Overview

D-SUB combination contact insert

D-SUB contact insert, wrap size 3, with 5 signal contacts, with solder cup, straight, housing for 4 combined contacts, female contact type, fixing by 3 mm drill, for recessed frame and VS-25 aerial housing-...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1655373

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 215 (C-2-2013)

GTIN 4046356029308

Weight per Piece (excluding packing) 15.050 g

Custom tariff number 85366990

Country of origin DE (Germany)

Mechanical characteristics

Number of positions 9

Connection profile 25-pos. D-SUB

Insertion/withdrawal cycles ≥ 200

Connection method Solder cup

Conductor cross section 0.5 mm^2

Connection cross section AWG 20

Insertion force per signal contact $\leq 3.40 \text{ N}$

Extraction force per signal contact $\geq 0.2 \text{ N}$

Mounting type Hole

Insulation resistance $\geq 5 \text{ G}\Omega$

Type 25

Size of housing 3

Type of note Order information:

Note The contacts must be ordered separately since they are not included in the scope of supply of the combi contact inserts.

Ambient conditions

Ambient temperature (operation) $-55 \text{ }^\circ\text{C} \dots 130 \text{ }^\circ\text{C}$

Material data

Flammability rating according to UL 94 V0

Housing material Steel, tin-plated

Contact carrier material PBT-GF

Contact material Copper alloy

Contact surface material Gold over nickel

Electrical characteristics

Number of positions 9

Rated current 5 A (at 20°C (signal contacts))

Overvoltage category III

Degree of pollution 2

Rated voltage (III/3) 250 V

Test voltage 1200 V

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloa..."

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-25-BU-DSUB-4P-5S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.