

INDUSTRIAL COMPONENT DATA

VS-25-ST-DSUB-LH-B 1654824 PHOENIX CONTACT D-SUB contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-25-ST-DSUB-LH-B



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-25-ST-DSUB-LH-B
Catalog number	1654824
Category	D-Sub connector
Minimum order	25 Pcs
Document ID	EO-7C0797CC0E
Generated	2026-08-02

Product Overview

D-SUB contact insert

D-SUB contact insert, wrap size 3, with 25 signal contacts, male contact type, for mounting on printed circuit boards, angled, fixing by drilling 2.5 mm and soldered sheet, for VS-25 recessed frame-...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1654824

Packing unit 25 pc

Minimum order quantity 25 pc

Catalog page Page 211 (C-2-2013)

GTIN 4017918989217

Weight per Piece (excluding packing) 14.110 g

Custom tariff number 85366990

Country of origin DE (Germany)

Mechanical characteristics

Number of positions 25

Connection profile 25-pos. D-SUB

Insertion/withdrawal cycles >= 200

Connection method Solder connection

Insertion force per signal contact ≤ 3.40 N

Mounting type Hole and solder metal plate

Type 25

Size of housing 3

Ambient conditions

Ambient temperature (operation) $-55\text{ }^{\circ}\text{C} \dots 125\text{ }^{\circ}\text{C}$

Material data

Flammability rating according to UL 94 V0

Housing material Steel

Housing surface material tin-plated

Contact surface material Au

Height 12.5 mm

Electrical characteristics

Number of positions 25

Rated current 5 A (at $20\text{ }^{\circ}\text{C}$)

Overvoltage category III

Degree of pollution 2

Rated voltage (III/3) 125 V

Test voltage 1200 V

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440302eCl@ss 8.027440302eCl@ss 9.027440205

ETIM 2.0EC000438ETIM 3.0EC000438ETIM 4.0EC000438ETIM 5.0EC001132ETIM 6.0EC000438

UNSPSC 6.0130211923UNSPSC 7.090139121522UNSPSC 1139121522UNSPSC 12.0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-25-ST-DSUB-LH-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.