

**INDUSTRIAL COMPONENT DATA**

# VS-15-T-2PG11 1688052 PHOENIX CONTACT D-SUB sleeve housings

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-15-T-2PG11



|                 |                                                   |
|-----------------|---------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                   |
| MPN / Reference | VS-15-T-2PG11                                     |
| Catalog number  | 1688052                                           |
| Category        | Accessories/spare parts for industrial connectors |
| Minimum order   | 5 Pcs                                             |
| Document ID     | EO-66D9BBC306                                     |
| Generated       | 2026-08-04                                        |

## Product Overview

D-SUB sleeve housings

D-SUB bobbin housing, wrap size 2, IP67 degree of protection

D-SUB mobile enclosure, tab size 2, IP67 degree of protection

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Field Device Connectors (FDC)

## Additional Product Information

Key Commercial Data

Orderkey 1688052

Packing unit 5 pc

Minimum order quantity 5 pc

Note Made to Order (non-returnable)

Catalog page Page 219 (C-2-2013)

GTIN 4017918179687

Weight per Piece (excluding packing) 38.290 g

Custom tariff number 85472000

Country of origin DE (Germany)

Mechanical characteristics

Insertion/withdrawal cycles &gt;= 1000

External cable diameter 3 mm ... 10 mm

Cable outlet Angled

Color gray

Degree of protection IP67

Type D-SUB 15

Size of housing 2

No. of cable outlets 2

Type of the screw connection Pg11

Ambient conditions

Ambient temperature (operation) -40 °C ... 80 °C

Material data

Flammability rating according to UL 94 V0

Housing material PA

Height 24 mm

Electrical characteristics

Degree of pollution 2

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss

7.027440202eCl@ss 8.027440202eCl@ss 9.027440202

ETIM 2.0EC000437ETIM 3.0EC000437ETIM 4.0EC000437ETIM 5.0EC000437ETIM 6.0EC000437

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC

13.231261501

ETIM for 1688052 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

68.4 mm

Height (EF000040)

24 mm

Depth (EF000049)

89 mm

Housing material (EF001596)

Plastic

Coating housing (EF001601)

Other

Housing...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-15-T-2PG11 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.