

INDUSTRIAL COMPONENT DATA

D-UK 4/10-NS 35 3003023 PHOENIX CONTACT End cover

Brand: PHOENIX CONTACT | Manufacturer Part Number: D-UK 4/10-NS 35



Manufacturer	PHOENIX CONTACT
MPN / Reference	D-UK 4/10-NS 35
Catalog number	3003023
Category	Endplate and partition plate for terminal block
Minimum order	50 Pcs
Document ID	EO-337CC23892
Generated	2026-08-05

Product Overview

End cover

End cap, with fixing foot for rail mounting, length: 50.6 mm, width: 1.8 mm, height: 46.5 mm, colour: grey, mounting class: NS 35/7.5

End cover, with snap-on foot for mounting on a DIN rail, depth: 46.5 mm, width: 1.8 mm, height: 50.6 mm, color: gray, mounting type: NS 35/7,5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type End cover

Data management status

Article revision 00

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (operation) 20 % ... 90 %

Permissible humidity (storage/transport) 30 % ... 70 %

MountingMounting type NS 35/7,5

NS 35/15

Material specificationsColor gray (RAL 7042)

Material PA 6.6

Flammability rating according to UL 94 V0

Static insulating material application in cold -60 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

DimensionsWidth 1.8 mm

Height 50.6 mm

Dep...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / D-UK 4/10-NS 35 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.