

INDUSTRIAL COMPONENT DATA

D3HC-MP 0.08-0.20-M-SN-L 1340367 PHOENIX CONTACT

Crimp Contact, Rated Current: 4 A, Surface Contacts: Tin

Brand: PHOENIX CONTACT | Manufacturer Part Number: D3HC-MP 0.08-0.20-M-SN-L



Manufacturer	PHOENIX CONTACT
MPN / Reference	D3HC-MP 0.08-0.20-M-SN-L
Catalog number	1340367
Category	Accessories/spare parts for industrial connectors
Minimum order	200 Pcs
Document ID	EO-A1F12389F7
Generated	2026-08-05

Product Overview

Crimp Contact, Rated Current: 4 A, Surface Contacts: Tin

Crimped contact

Crimp contact, nominal current: 4 A, contact surface: Tin

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type Crimp contact

Product family D3HC-MP-M

Pitch 0 mm

Connection dataStripping length 4.5 mm

Conductor cross section AWG 28 ... 24

Material specificationsContact surface Tin Sn

Contact surface material Tin

Metal surface terminal point (top layer) Tin (1 - 3 µm Sn)

Metal surface contact area (top layer) Tin (1 - 3 µm Sn)

DimensionsPitch 0 mm

Electrical propertiesNominal current IN 4 A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / D3HC-MP 0.08-0.20-M-SN-L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.