

INDUSTRIAL COMPONENT DATA

MINI-PS- 12- 24DC/ 5-15DC/2 2320018 PHOENIX CONTACT

DC/DC converters

Brand: PHOENIX CONTACT | Manufacturer Part Number: MINI-PS-12-24DC/ 5-15DC/2



Manufacturer	PHOENIX CONTACT
MPN / Reference	MINI-PS-12-24DC/ 5-15DC/2
Catalog number	2320018
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-E4374AB0C2
Generated	2026-08-03

Product Overview

DC/DC converters

For new installations use the following item: 1066704.Primary switched MINI DC/DC converter for rail mounting, input: 12 - 24 V DC, output: 5 - 15 V DC/2 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Power Supplies (PS)

Additional Product Information

Key Commercial Data

Orderkey 2320018

Packing unit 1 pc

Catalog page Page 256 (C-4-2017)

GTIN 4046356478519

Weight per Piece (excluding packing) 200.000 g

Custom tariff number 85044030

Country of origin CN (China)

Dimensions

Width 22.5 mm

Height 99 mm

Depth 107 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -25 °C ... 70 °C (> +60°C derating)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) ≤ 95 % (At +25°C, non-condensing)

Climatic class 3K3 (in acc. with EN 60721)

Degree of pollution 2

Input data

Nominal input voltage range 12 V DC ... 24 V DC

Input voltage range 10 V DC ... 32 V DC (> 10.5 V DC start)

Frequency range DC 0 Hz

Current consumption 2.3 A (12 V DC)

1.1 A (24 V DC)

Inrush surge current < 10 A (typical)

Mains buffering typ. 4 ms (12 V DC)

typ. 18 ms (24 V DC)

Input fuse 6.3 A (slow-blow, internal)

Output data

Nominal output voltage 12 V DC ±1 %

Setting range of the output voltage (USet) 5 V DC ... 15 V DC

Nominal output current (IN) 2 A (-25 °C ... 60 °C)

Derating 60 °C ... 70 °C (2.5%/K)

Connection in parallel Yes, for assembling redundant systems and increasing efficiency

Connection in series yes

Feedback resistance 30 V DC

Output overvoltage protection < 25 V DC

Residual ripple < 20 mVPP(20 MHz)

Typical response time < 0.5 s

Peak switching voltages nominal load < 10 mVPP(20 MHz)

Maximum power dissipation in no-load condition < 1 W

Power loss nominal load max. < 4.2 W

Genera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MINI-PS-12-24DC/ 5-15DC/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.