

INDUSTRIAL COMPONENT DATA

DD21H 0,85/16-V-2,5-Y 1378121 PHOENIX CONTACT Printed circuit board base housing, color: black, rated curren..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DD21H 0,85/16-V-2,5-Y



Manufacturer	PHOENIX CONTACT
MPN / Reference	DD21H 0,85/16-V-2,5-Y
Catalog number	1378121
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-89AC560364
Generated	2026-08-05

Product Overview

Printed circuit board base housing, color: black, rated current: 5 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Male, number of rows: 2, number of poles: 16, item family: DD21H 0.85/.. -V, pitch: 2.5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: CONNEXIS DD, Plug-in face orientation: Standard, locking: Snap-in lock, clamping type: Socket protrusion, packaging type: boxed

PCB base housing, color: black, rated current: 5 A, rated voltage (III/2): 160 V, surface contacts: tin, contact type: Male, number of rows: 2, number of poles: 16, item family: DD21H 0.85/.. -V, pitch: 2.5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: CONNEXIS DD, Plug-in Face Orientation: Standard, Locking: Snap Lock, Attachment Type: Lace Protrusion, Packing Type: Boxed Packaging

PCB headers, color: black, nominal current: 5 A, rated voltage (III/2): 160 V, contact surface: Tin, contact connection type: Pin, number of rows: 2, number of positions: 16, product range: DD21H 0,85/..-V, pitch: 2.5 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: CONNEXIS DD, Pin connector pattern align...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct line CONNEXIS Connectors XS

Product type PCB headers

Product family DD21H 0,85/..-V

Number of positions 16

Pitch 2.5 mm

Number of rows 2

Pin layout Linear pinning

Solder pins per potential 1

Electrical propertiesNominal current IN 5 A

Nominal voltage UN 160 V

Degree of pollution 3

Contact resistance 2 mΩ

Rated voltage (III/3) 40 V

Rated surge voltage (III/3) 2.5 kV

Rated voltage (III/2) 160 V

Rated surge voltage (III/2) 2.5 kV

Rated voltage (II/2) 200 V

Rated surge voltage (II/2) 2.5 kV

MountingMounting type Wave soldering

Pin layout Linear pinning

Material specificationsMaterial data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics Tin-plated

Metal surface contact area (top layer) Tin (3 - 5 μm Sn)

Metal surface contact area (middle layer) Nickel (1.3 - 3 μm Ni)

Metal surface soldering area (top layer) Tin (3 - 5 μm Sn)

Metal surface soldering area (middle layer) Nickel (1.3 - 3 μm Ni)

Material data - housing

Color (Housing) black (9005)

Insulating material PBT

Insulating material group II

CTI according to IEC 60112 400 ≤ CTI

Flammability rating according to UL 94 V0

NotesNote on the contact These connectors conform to DIN EN 61984, connectors without switching capacity (COC). When used for their intended purpose, they must not be plugged in or disconnected live or under load.

DimensionsDimensional drawing

Pitch 2.5 mm

Width [w] 22.7 mm

He...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DD21H 0,85/16-V-2,5-Y with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.