


INDUSTRIAL COMPONENT DATA

CBB 04 2X2RC-PT 2905238 PHOENIX CONTACT Potential distributors

Brand: PHOENIX CONTACT | Manufacturer Part Number: CBB 04 2X2RC-PT



Manufacturer	PHOENIX CONTACT
MPN / Reference	CBB 04 2X2RC-PT
Catalog number	2905238
Category	Fuse terminal block
Minimum order	1 Pcs
Document ID	EO-08278064D0
Generated	2026-08-03

Product Overview

Potential distributors

Equipment protection switch plates for four circuit breakers (CB TM1...) or electronic (CB E1... NO) with collective remote indication, central power supply, connection for relay contacts and potential distribution for up to four consumers per channel.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Over Current Protection**

Additional Product Information

Key Commercial Data

Orderkey 2905238

Packing unit 1 pc

Catalog page Page 259 (C-6-2015)

GTIN 4046356935388

Weight per Piece (excluding packing) 264.810 g

Custom tariff number 85363090

Country of origin DE (Germany)

Dimensions

Height 127.8 mm

Width 108.5 mm

Depth 70.8 mm

Ambient conditions

Ambient temperature (operation) -30 °C ... 60 °C

Ambient temperature (storage/transport) -30 °C ... 80 °C

Humidity test 96h, 93% RH, 40 °C

Degree of protection IP20 (Terminal blocks and fuse holders)

IP00 (PCB)

General

Flammability rating according to UL 94 V0

Mounting type DIN rail: 35 mm

Number of positions 4

Overvoltage category_GRP II

Protection class III

Degree of pollution 2

Type DIN rail module, two-section, divisible

Electrical data

Rated voltage main circuit 24 V DC

Rated current main circuit 48 A DC (total)

12 A DC (per channel)

Rated voltage remote indication circuit 24 V DC

Rated current remote indication circuit 0.5 A DC

Rated surge voltage 0.5 kV

Short circuit stability 600 A (conditional according to DIN EN 50178)

Power dissipation 4.1 W (without circuit breaker)

Insertion/withdrawal cycles 50

Connection data

Connection name Supply X21

Connection method Push-in connection

Stripping length 18 mm

Conductor cross section solid 0.75 mm² ... 16 mm²

Conductor cross section AWG 20 ... 4

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.75 mm² ... 10 mm²Conductor cross section flexible, with ferrule without plastic sleeve 0.75 mm² ... 16 mm²

Connection name Outp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CBB 04 2X2RC-PT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.