

INDUSTRIAL COMPONENT DATA

CA-09P1N12AD00 1621746 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-09P1N12AD00



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-09P1N12AD00
Catalog number	1621746
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-38C5D82689
Generated	2026-08-01

Product Overview

Device connector, front mounting

M23, Conect. plug. to be apar. front wall, RC, Swivel angle, shielded: yes, for standard lock and SPEEDCON, No. of poles: 8+1, Rotation direction: Standard, contact type: Male, Solder connection, Axial O-ring, 4x Ø 3.2, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1244478

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1621746

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 96 (C-2-2017)

GTIN 4055626001210

Weight per Piece (excluding packing) 111.110 g

Custom tariff number 85366990

Country of origin DE (Germany)

Data of the insulating body

Coding N

Insulator material PBT

Contact material CuZn
Contact surface material Ni/Au
Insertion/withdrawal cycles mechanical 100
Contact connection method Solder connection
Type of contacts Pin
Application Signal
Number of positions 9
Contact diameter of power contacts 2 mm
Litz wire cross section of power contacts max. 2.5 mm²
Nominal current per power contact at 25°C 20 A
Nominal voltage, power contact 300 V
Rated surge voltage 2.5 kV
Overvoltage category II
Degree of pollution 3
Contact diameter of signal contacts 1 mm
Litz wire cross section of signal contacts max. 1 mm²
Nominal current per signal contact at 25°C 8 A
Nominal voltage, signal contact 300 V
Overvoltage category II
Degree of pollution 3
Housing data
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking for standard and SPEEDCON interlock
Degree of protection (when plugged in) IP67
Thread type M23
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 10.0.127371392eCl@ss 5.127379100eCl@ss 6.027379200eCl@ss 7.02737...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-09P1N12AD00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.