

INDUSTRIAL COMPONENT DATA

SH-8ESC58AWA00S 1621567 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: SH-8ESC58AWA00S



Manufacturer	PHOENIX CONTACT
MPN / Reference	SH-8ESC58AWA00S
Catalog number	1621567
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-BB115E6BE9
Generated	2026-08-03

Product Overview

Device connector, front mounting

M23, Conect. plug. to be apar. front wall, SH, straight, shielded: yes, for standard lock and SPEEDCON, No. of poles: 4+4+4+PE / 3+N+PE, Direction of rotation: Standard, contact type: Female, Crimped connection, Axial O-ring, 4x Ø 3.2, flange measurement: 26mm x 26mm, coding:N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1621567

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 117 (C-2-2017)

GTIN 4046356937153

Weight per Piece (excluding packing) 40.700 g

Custom tariff number 85366990

Country of origin DE (Germany)

Temperature range

Ambient temperature (operation) -40 °C ... 130 °C

Data of the insulating body

Note Order information: Crimp contacts, 4x Ø 0.8 mm, 4x Ø 1 mm, 5x Ø 2 mm, order separately

Data rate 100 Mbps

Coding N

Insulator material PA 6.6

Insertion/withdrawal cycles mechanical 100

Contact connection method Crimp connection

Type of contacts Socket

Application Hybrid

Number of positions 13

Contact diameter of power contacts 2 mm

Litz wire cross section of power contacts min. 0.25 mm²

Litz wire cross section of power contacts max. 4 mm²

Nominal current per power contact at 25°C 30 A

Rated surge voltage 6 kV

Rated voltage (II/3) power contact 850 V DC

Rated voltage (III/3) power contact 630 V[~]AC

Contact diameter of signal contacts 1 mm

Litz wire cross section of signal contacts min. 0.06 mm²

Litz wire cross section of signal contacts max. 1 mm²

Nominal current per signal contact at 25°C 8 A

Rated surge voltage 1.5 kV

Rated voltage (III/3) signal contact 50 V

Contact diameter, data contacts 0.8 mm

Litz wire cross section, data contacts, min. 0.08 mm²

Litz wire cross section, data contacts, max. 0.5 mm²

Nominal current per data contact at 25°C 3.6 A

Nominal voltage of data contact 50 V

Rated surge voltage 1.5 kV

Rated voltage (III/3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SH-8ESC58AWA00S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.