

INDUSTRIAL COMPONENT DATA

CA-07S1NC22S00 1619914 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-07S1NC22S00



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-07S1NC22S00
Catalog number	1619914
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-A353AE2A57
Generated	2026-08-04

Product Overview

Device connector, front mounting

M23, Conect. plug. to be apar. front wall, AC, straight, shielded: yes, for standard and SPEEDCON locking, No. of poles: 7, Direction of rotation: Standard, contact type: Female, Weld connection, Flat joint, 4x Ø 3.2, flange size: 25 mm x 25 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1243892

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1619914

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 330 (C-2-2013)

GTIN 4046356820530

Weight per Piece (excluding packing) 27.700 g

Custom tariff number 85366990

Country of origin DE (Germany)

Temperature range

Ambient temperature (operation) -40 °C ... 125 °C

Dimensions

free solder pin length 17.5 mm
Data of the insulating body
Coding N
Insulator material PBT
Contact material CuZn
Contact surface material Ni/Au
Contact connection method Solder-in connection
Type of contacts Socket
Application Signal
Number of positions 7
Contact diameter of power contacts 2 mm
Nominal current per power contact at 25°C 20 A
Nominal voltage, power contact 300 V
Rated surge voltage 2.5 kV
Overvoltage category II
Degree of pollution 3
Overvoltage category II
Degree of pollution 3
Housing data
Housing material CuZn
Flange dimensions 25 mm x 25 mm
Type of locking for standard and SPEEDCON interlock
Degree of protection (when plugged in) IP67
Thread type M23
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102
ETIM 3.0EC001121ETIM 4.0EC002635ETIM 5.0EC002061ETIM 6.0EC002061
UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 11431720...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-07S1NC22S00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.