

INDUSTRIAL COMPONENT DATA

CA-12P1N8A2S00 1619966 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-12P1N8A2S00



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-12P1N8A2S00
Catalog number	1619966
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-4418B896CF
Generated	2026-08-03

Product Overview

Device connector, front mounting

M23, Conect. plug. to be apar. front wall, AC, straight, shielded: yes, for standard and SPEEDCON locking, No. of poles: 12, Rotation direction: Standard, contact type: Male, Crimped connection, Flat joint, 4x Ø 3.2, flange size: 25 mm x 25 mm, coding:N

M23, Device connector front mounting, series: CA, straight, shielded: yes, for standard and SPEEDCON interlock, No. of pos.: 12, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, Flat gasket, 4x Ø 3.2, flange dimensions: 25 mm x 25 mm, coding: N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesOrder information: Order 12 x 1 mm crimp contacts separately

Product propertiesProduct type Circular connectors (device side)

Data management status

Article revision 07

ConnectorInsulating body

Note Order information: Order crimp contacts Ø 1 mm separately

Coding N

Insulation body material PA 6.6

Connection method Crimp connection

Contact switching type Pin
Application Signal
Number of positions 12
Direction of rotation Standard
Connection profile 12
Contact diameterSignal contacts 1 mm
Litz wire cross-sectionSignal contactsmin. 0.08 mm²
Litz wire cross-sectionSignal contactsmax. 1 mm²
Nominal current per signal contact 8 A
Rated voltage Signal contact 48 V AC
Rated surge voltage 1.5 kV
Overvoltage category III
Degree of pollution 3
Housing
Housing material GD-Zn
Flange dimensions 25 mm x 25 mm
Type of locking for standard and SPEEDCON interlock
Pg screw connection none
Degree of protection (plugged in) IP67
Thread type M23
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -40 °C ... 125 °C
Ambient temperature (storage/transport) 15 °C ... 25 °C
Permissible humidity (storage/transport) 50 % ... 65 %
ETIM for 1619966 Connectors (EC002635)
Feature Name
Feature Value
Number of data contacts (EF012232)
0
Number of power contacts (EF012216)
0
Ambient temperature (EF002386)
-40 °C
Type of locking (EF000208)
Other
With protective conductor (EF007468)
No
Screened (EF000881)
No
With status indication (EF001602)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-12P1N8A2S00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.