

## INDUSTRIAL COMPONENT DATA

# CA-12P1N8AHZ00 1619787 PHOENIX CONTACT Device connector, rear mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-12P1N8AHZ00



|                 |                                              |
|-----------------|----------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                              |
| MPN / Reference | CA-12P1N8AHZ00                               |
| Catalog number  | 1619787                                      |
| Category        | Circular connector, mounting (without cable) |
| Minimum order   | 1 Pcs                                        |
| Document ID     | EO-E2DF967A78                                |
| Generated       | 2026-08-05                                   |

## Product Overview

Device connector, rear mounting

M23, Conect. plug. to be apar. poster wall., AC, straight, shielded: yes, for standard lock and SPEEDCON, No. of poles: 12, Direction of rotation: Standard, contact type: Male, Crimped connection, Axial joint, Central fixing, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1243839

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Field Device Connectors (FDC)

## Additional Product Information

Key Commercial Data

Orderkey 1619787

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 94 (C-2-2017)

GTIN 4046356821308

Weight per Piece (excluding packing) 43.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

Temperature range

Ambient temperature (operation) -40 °C ... 125 °C

Data of the insulating body

Note Order information: Order crimp contacts Ø 1 mm separately

Coding N

Insulator material PA 6.6

Contact connection method Crimp connection

Type of contacts Pin

Application Signal

Number of positions 12

Contact diameter of signal contacts 1 mm

Litz wire cross section of signal contacts min. 0.08 mm<sup>2</sup>

Litz wire cross section of signal contacts max. 1 mm<sup>2</sup>

Nominal current per signal contact at 25°C 8 A

Nominal voltage, signal contact 150 V

Rated surge voltage 1.5 kV

Overvoltage category II

Degree of pollution 3

Housing data

Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)

Type of locking for standard and SPEEDCON interlock

Degree of protection (when plugged in) IP67

Thread type M23

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss

7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 3.0EC001121ETIM 4.0EC002635ETIM 5.0EC002061ETIM 6.0E...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-12P1N8AHZ00 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.