

INDUSTRIAL COMPONENT DATA

ST-08S1N8AW500S 1619220 PHOENIX CONTACT Device connector, rear mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-08S1N8AW500S



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-08S1N8AW500S
Catalog number	1619220
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-E5E6276316
Generated	2026-08-04

Product Overview

Device connector, rear mounting

Connect. plug. to be apar. front wall, straight, for standard and SPEEDCON locking, M17, number of poles: 8, contact type: Female, Axial O-ring, 4x Ø 3.2, shielded: yes, flange size: 25.75 mm x 25.75 mm, protection index: IP67, number of poles: 8, connection type: Crimped connection, series: ST

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1619220

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 67 (C-2-2017)

GTIN 4046356827492

Weight per Piece (excluding packing) 33.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Note Order information: Order crimp contacts Ø 1 mm separately

Type of locking for standard and SPEEDCON interlock

Direction of rotation of contact chamber numbering Standard

Coding N

Contact connection method Crimp connection

Type of contacts Socket

Number of positions 8

Contact diameter of power contacts 1 mm

Nominal current per power contact at 25°C 8 A

Pg housing screw connection none

Mounting type 4x Ø 3.2

Ambient conditions

Ambient temperature -40 °C ... 125 °C

Degree of protection IP67

Specifications according to DIN EN 61984:2001

Installation height max. 3000 mm

Nominal / operating voltage of power contacts 60 V

Rated surge voltage of power contacts 1.5 kV

Overvoltage category of power contacts III

Degree of pollution of power contacts 3

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss

7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 3.0EC001121ETIM 4.0EC002635ETIM 5.0EC002061ETIM 6.0EC002061

UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.01432014...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-08S1N8AW500S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.