

INDUSTRIAL COMPONENT DATA

SFP 1-5/120AC 2920667 PHOENIX CONTACT EMC filter surge protection device

Brand: PHOENIX CONTACT | Manufacturer Part Number: SFP 1-5/120AC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SFP 1-5/120AC
Catalog number	2920667
Category	Surge protection device for terminal equipment
Minimum order	1 Pcs
Document ID	EO-16D72D904F
Generated	2026-08-01

Product Overview

EMC filter surge protection device

Device protection, according to type 3/class III, with mains parasitic filter against high-frequency edging voltages, for single-phase power supply networks with separate N and PE (3-conductor system: L1, N, PE), with remote indication contact.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2920667

Packing unit 1 pc

Catalog page Page 185 (C-4-2017)

GTIN 4046356158558

Weight per Piece (excluding packing) 571.280 g

Custom tariff number 85363010

Country of origin DE (Germany)

Dimensions

Height 86.6 mm

Width 112 mm

Depth 79 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -25 °C ... 70 °C

Ambient temperature (storage/transport) -25 °C ... 70 °C

Permissible humidity (operation) 5 % ... 95 %

General

EN type T3

Number of ports Two

Mode of protection L-N

L-PE

N-PE

Mounting type DIN rail: 35 mm

Color black

silver

Housing material Aluminum

Degree of pollution 2

Flammability rating according to UL 94 V-0

Type DIN rail module, one-piece

Number of positions 2

Surge protection fault message Optical, remote indicator contact

For country-specific use in USA, CN, BR

Protective circuit

Nominal voltage UN 120 V AC (TN)

120 V AC (TT - only in use with RCD)

120 V AC (IT)

Nominal frequency fN 50 Hz (60 Hz)

Maximum continuous voltage UC 150 V AC

Rated load current IL 5 A (70°C)

Residual current IPE ≤ 0.6 mA

Nominal discharge current In(8/20) μs 3 kA

Standby power consumption PC ≤ 7.5 VA (at UREF)

≤ 10 VA (at UC)

Reference test voltage UREF 132 V AC

Combination wave UOC 6 kV (3 kA)

Voltage protection level Up ≤ 0.45 kV

TOV behavior at UT(L-N) 175 V AC (5 s / withstand mode)

240 V AC (5 s / safe failure mode)

208 V AC (120 min / safe failure mode)

TOV behavior at UT(L-PE) 208 V AC (5 s / withstand mode)

175 V AC (120 min / wit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SFP 1-5/120AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.