

INDUSTRIAL COMPONENT DATA

G 5/ 4 2716046 PHOENIX CONTACT Device terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: G 5/ 4



Manufacturer	PHOENIX CONTACT
MPN / Reference	G 5/ 4
Catalog number	2716046
Category	Single- and multi-pole terminal strip
Minimum order	50 Pcs
Document ID	EO-7C203E96C3
Generated	2026-08-02

Product Overview

Device terminal block

Device terminal, nominal voltage: 500 V, nominal current: 32 A, number of connections: 8, number of poles: 4, connection type: Screw connection, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 4 mm², mounting class: direct screwed, color: gray

Device terminal block, nom. voltage: 500 V, nominal current: 32 A, number of connections: 8, number of positions: 4, connection method: Screw connection, Rated cross section: 4 mm², cross section: 0.2 mm² - 4 mm², mounting type: direct screw connection, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Feed-through terminal block

Number of positions 4

Number of connections 8

Number of rows 1

Potentials 4

Data management status

Article revision 05

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Rated surge voltage 6 kV
Maximum power dissipation for nominal condition 1.02 W
Connection data Number of connections per level 8
Nominal cross section 4 mm²
Screw thread M3
Tightening torque 0.6 ... 0.8 Nm
Stripping length 8 mm
Internal cylindrical gage A3
Connection in acc. with standard IEC 60947-7-1
Conductor cross section rigid 0.2 mm² ... 4 mm²
Cross section AWG 24 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.2 mm² ... 4 mm²
Conductor cross section, flexible [AWG] 24 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 4 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 2.5 mm²
2 conductors with same cross section, solid 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1 mm²
Nominal current 32 A
Maximum load current 32 A (with 4 mm² conductor cross section)
Nominal voltage 500 V
Nominal cross section 4 mm²
Dimensions Dimensional drawing
Width....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G 5/ 4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.