

INDUSTRIAL COMPONENT DATA

GE 35/2 BU 3071078 PHOENIX CONTACT Device terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: GE 35/2 BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	GE 35/2 BU
Catalog number	3071078
Category	Single- and multi-pole terminal strip
Minimum order	25 Pcs
Document ID	EO-EFF943E761
Generated	2026-07-31

Product Overview

Device terminal block

Device terminal, connection type: Screw connection, number of connections: 4, number of poles: 2, cross-section: 0.75 mm² - 35 mm², AWG: 18 - 2, width: 34.8 mm, height: 44.9 mm, color: blue, mounting class: Direct screwing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 3071078

Packing unit 25 pc

Minimum order quantity 25 pc

Note Made to Order (non-returnable)

Catalog page Page 561 (C-1-2017)

GTIN 4046356482363

Weight per Piece (excluding packing) 108.000 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of positions 2

Number of levels 1

Number of connections 4
Potentials 2
Nominal cross section 35 mm²
Color blue
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 4.06 W
Maximum load current 125 A (with 35 mm² conductor cross section)
Nominal current I_N 125 A
Nominal voltage U_N 630 V
Open side panel No
Dimensions
Width 34.8 mm
Length 83.7 mm
Height 44.9 mm
Connection data
Note Terminal point
Connection method Screw connection
Screw thread M6
Stripping length 16 mm
Tightening torque, min 3.5 Nm
Tightening torque max 4 Nm
Connection in acc. with standard IEC 60947-7-1/IEC 60998
Conductor cross section solid min. 0.75 mm²
Conductor cross section solid max. 35 mm²
Conductor cross section AWG min. 18
Conductor cross section AWG max. 2
Conductor cross section flexible min. 0.75 mm²
Conductor cross section flexible max. 35 mm²
Min. AWG conductor cross section, flexible 18
Max. AWG conductor cross section, flexible 2
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.75 mm²
Conductor cross section flexible, wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GE 35/2 BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.