


INDUSTRIAL COMPONENT DATA

DFK-MSTB 2,5/ 2-G OG CR1 1768392 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-MSTB 2,5/ 2-G OG CR1



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-MSTB 2,5/ 2-G OG CR1
Catalog number	1768392
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-F341CBA192
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Feed-through housing, nominal section: 2.5 mm², color: orange, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: DFK-MSTB 2.5/.. -G, pitch: 5 mm, connection type: Solder/flat plug connection, mounting: Direct mounting, pin arrangement: Linear pin arrangement, pin length [P]: 9.3 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1768392

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356440608

Weight per Piece (excluding packing) 3.590 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 17.5 mm

Width 30 mm

Pitch 5 mm

Dimension a 5 mm

Width [w] 30 mm

Height [h] 29.5 mm

Height 20.2 mm

Length of the solder pin 9.3 mm

Length 17.5 mm

General

Range of articles DFK-MSTB 2,5/..-G

Rated voltage (III/3) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Color orange

Number of positions 2

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141111eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss

7.027141134eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002637ETIM 6.0EC001283

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC

13.239121410

ETIM for 1768392 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

2

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5 mm

Modular spacing connections (EF006827)

5 mm

Rated current In (EF008250)

12 A

Rated voltage (EF000228)

320 V

Rated surg...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-MSTB 2,5/ 2-G OG CR1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.