

INDUSTRIAL COMPONENT DATA

DFK-MSTB 2,5/ 9-G WW(1X1) 0708179 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-MSTB 2,5/ 9-G WW(1X1)



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-MSTB 2,5/ 9-G WW(1X1)
Catalog number	0708179
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-D8FFE96318
Generated	2026-08-04

Product Overview

Printed-circuit board connector

Wall pass-through housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Male, Number of rows: 1, Number of poles per row: 9, article family: DFK-MSTB 2.5/..-G, pitch: 5 mm, connection type: Solder/flat plug connection, mounting: Direct mounting, pin length [P]: 9.3 mm, Stecksystem: CLASSIC COMBICON, Locking: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 0708179

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4017918004491

Weight per Piece (excluding packing) 8.200 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [L] 17.5 mm

Width 65 mm

Pitch 5 mm

Dimension a 40 mm

Width [w] 65 mm

Height [h] 29.5 mm

Height 20.2 mm

Length of the solder pin 9.3 mm

Length 17.5 mm

General

Range of articles DFK-MSTB 2,5/..-G

Rated voltage (III/3) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Color green

Number of positions 9

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0 272607xx eCl@ss 4.1 27260701 eCl@ss 5.0 27260701 eCl@ss 5.1 27141100 eCl@ss 6.0 27141100 eCl@ss 7.0 27141134 eCl@ss 8.0 27440402 eCl@ss 9.0 27440402

ETIM 3.0 EC000897 ETIM 4.0 EC001283 ETIM 5.0 EC002637 ETIM 6.0 EC001283

UNSPSC 6.01 30211810 UNSPSC 7.0901 39121409 UNSPSC 11 39121409 UNSPSC 12.01 39121409 UNSPSC 13.2 39121410

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-MSTB 2,5/ 9-G WW(1X1) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.