

**INDUSTRIAL COMPONENT DATA**

# DFK-PC 4/12-G-7,62-LOE 1830842 PHOENIX CONTACT

## Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-PC 4/12-G-7,62-LOE



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | DFK-PC 4/12-G-7,62-LOE          |
| Catalog number  | 1830842                         |
| Category        | Printed circuit board connector |
| Minimum order   | 50 Pcs                          |
| Document ID     | EO-DD77CDBBF8                   |
| Generated       | 2026-08-03                      |

### Product Overview

Feed-through header

Wall pass-through housing, nominal section: 4 mm<sup>2</sup>, color: green, nominal current: 15 A, nominal voltage (III/2): 400 V, contact surface: Tin, contact type: Male, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, family of articles: DFK-PC 4/.. -G -LOE, pitch: 7.62 mm, connection type: Solder connection, mounting: Solder, pin arrangement: Linear pin arrangement, pin length [P]: 5.87 mm, number of solder pins per potential: 2, plug-in system: COMBICON PC 4, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; PCB Connectors (PCC)

### Additional Product Information

Key Commercial Data

Orderkey 1830842

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4017918051488

Weight per Piece (excluding packing) 22.730 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [ L ] 34.87 mm

Width 106.66 mm

Pitch 7.62 mm

Dimension a 83.82 mm

Width [ w ] 106.66 mm

Height [ h ] 14.25 mm

Height 14.25 mm

Length 34.87 mm

General

Range of articles DFK-PC 4/...-G -LOE

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 400 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 800 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 15 A

Insulating material PA

Color green

Number of positions 12

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC

13.239121409

ETIM for 1830842 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

12

Number of plug-in contact rows (EF006935)

1

Modular spacing contact...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-PC 4/12-G-7,62-LOE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.