


INDUSTRIAL COMPONENT DATA

DFK-PC 4/ 6-GF-7,62 BD:6-1 1723515 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-PC 4/ 6-GF-7,62 BD:6-1



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-PC 4/ 6-GF-7,62 BD:6-1
Catalog number	1723515
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-4B03AEA367
Generated	2026-08-04

Product Overview

Printed-circuit board connector

Wall pass-through terminal, nominal section: 4 mm², color: green, nominal current: 20 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, family of articles: DFK-PC 4/.. -GF, pitch: 7.62 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, mounting: Direct mounting, conductor/printed circuit board connection direction: 0 °, number of solder pins per potential: 1, plug-in system: COMBICON PC 4, Plug-in face orientation: Standard, lock: Screw lock, Attachment Type: Overhead Clamping (Thread), Packing Type: Boxed Packed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1723515

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4046356122511

Weight per Piece (excluding packing) 26.000 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Pitch 7.62 mm

Dimension a 38.1 mm

General

Range of articles DFK-PC 4/...-GF

Number of positions 6

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 400 V

Connection in acc. with standard EN-VDE

Nominal current IN 20 A

Nominal cross section 4 mm²

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 10

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 2.5 mm²

2 conductors with same cross section, stranded min. 0.2 mm²

2 conductors with same cross section, stranded max. 2.5 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.2 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, max....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-PC 4/ 6-GF-7,62 BD:6-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.