


INDUSTRIAL COMPONENT DATA

DFMC 0,5/ 8-ST-2,54 1844633 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFMC 0,5/ 8-ST-2,54



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFMC 0,5/ 8-ST-2,54
Catalog number	1844633
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-2A99A9CC8A
Generated	2026-08-02

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 0.5 mm², color: black, nominal current: 6 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Female, number of potentials: 16, number of rows: 2, number of poles: 8, number of connections: 16, article family: DFMC 0.5/. -ST, pitch: 2.54 mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, plug-in system: COMBICON DFMC 0.5, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1844633

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356964319

Weight per Piece (excluding packing) 3.970 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 15.85 mm

Width [w] 20.82 mm

Height [h] 10.5 mm

Pitch 2.54 mm

Dimension a 17.78 mm

General

Range of articles DFMC 0,5/...-ST

Number of positions 8

Connection method Push-in spring connection

Insulating material group IIIa

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 32 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 160 V

Connection in acc. with standard EN-VDE

Nominal current I_N 6 A

Nominal cross section 0.5 mm²

Maximum load current 6 A

Insulating material LCP

Flammability rating according to UL 94 V0

Stripping length 7 mm

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 0.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 0.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 0.34 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.14 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.25 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 20

Standards and R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFMC 0,5/ 8-ST-2,54 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.