


INDUSTRIAL COMPONENT DATA

DFMC 1,5/12-ST-3,5-LR2BKBD:QSO 1707648 PHOENIX CONTACT Plug-in part, rated current: 8 A, number of poles: 12..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFMC 1,5/12-ST-3,5-LR2BKBD:QSO



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFMC 1,5/12-ST-3,5-LR2BKBD:QSO
Catalog number	1707648
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-D042CD55EF
Generated	2026-08-04

Product Overview

Plug-in part, rated current: 8 A, number of poles: 12, pitch: 3.5 mm, connection type: Push-in spring connection, color: black, contact surface: Tin

Connector for printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 24, number of rows: 2, number of poles: 12, number of connections: 24, family of articles: DFMC 1.5/..-ST, pitch: 3.5mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, plug-in system: COMBICON DFMC 1.5, lock: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross section: 1.5 mm², color: black, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Socket, number of potentials: 24, number of rows: 2, number of positions: 12, number of connections: 24, product range: DFMC 1,5/..-ST-LR, pitch: 3.5 mm, connection method: Push-in spring connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON DFMC 1,5, locking: without, mounting: without, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct type PCB connector
Product family DFMC 1,5/..-ST-LR

Product line COMBICON Connectors S

Type Plug component

Number of positions 12

Pitch 3.5 mm

Number of connections 24

Number of rows 2

Number of potentials 24

Mounting flange without

Data management status

Article revision 05

Electrical propertiesNominal current IN 8 A

Nominal voltage UN 160 V

Contact resistance 2 mΩ

Rated voltage (III/3) 160 V

Rated surge voltage (III/3) 2.5 kV

Rated voltage (III/2) 160 V

Rated surge voltage (III/2) 2.5 kV

Rated voltage (II/2) 320 V

Rated surge voltage (II/2) 2.5 kV

Connection dataConnection technology

Type Plug component

Connector system COMBICON DFMC 1,5

Nominal cross section 1.5 mm²

Contact connection type Socket

Interlock

Locking type without

Mounting flange without

Conductor connection

Connection method Push-in spring connection

Conductor/PCB connection direction 0 °

Conductor cross section rigid 0.2 mm² ... 1.5 mm²

Conductor cross section flexible 0.2 mm² ... 1.5 mm²

Conductor cross section AWG 24 ... 16

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.14 mm² ... 0.75 mm²

Cylindrical gauge a x b / diameter 2.4 mm x 1.5 mm / 1.6 mm

Stripping length 10 mm

Specifications for ferrules without insulating collar

recommended crimping tool 1212034 CRIMPFOX 6

ferrules without insulating collar, according to DIN 46228-1 Cross section: 0.25 mm²;....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFMC 1,5/12-ST-3,5-LR2BKBD:QSO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.