

**INDUSTRIAL COMPONENT DATA**

# DFMC 1,5/15-STF-3,5 BK 1469114 PHOENIX CONTACT Printed circuit board connector, nominal section: 1.5 mm<sup>2</sup>, co..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFMC 1,5/15-STF-3,5 BK



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | PHOENIX CONTACT        |
| MPN / Reference | DFMC 1,5/15-STF-3,5 BK |
| Catalog number  | 1469114                |
| Category        | Cable connector        |
| Minimum order   | 50 Pcs                 |
| Document ID     | EO-268030D493          |
| Generated       | 2026-08-02             |

## Product Overview

Printed circuit board connector, nominal section: 1.5 mm<sup>2</sup>, color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Female, number of rows: 2, number of poles: 15, article family: DFMC 1.5/..-STF, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Insert in base strip, driver/printed circuit board connection direction: 0 °, plug-in system: COMBICON DFMC 1.5, lock: Screw lock, clamping type: Air clamp (screw), packaging type: boxed  
 Plug-in connector for circ board. printed

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; PCB Connectors (PCC)

## Additional Product Information

ETIM for 1469114 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of plug-in contact rows (EF006935)

2

Modular spacing contacts (EF007326)

3.5 mm  
Modular spacing connections (EF006827)  
3.5 mm  
Angle contact/conductor connection (EF007546)  
Other  
Rated current  $I_n$  (EF008250)  
8 A  
Rated voltage (EF000228)  
160 V  
Rated surge voltage (EF002993)  
2.5 kV  
Over voltage category (EF006785)  
III  
Pollution degree (EF006786)  
2  
Connectable conductor cross section fine-strand without cable end sleeve (EF007341)  
0.2 mm<sup>2</sup>  
Connectable conductor cross section fine-strand with cable end sleeve (EF007339)  
0.25 mm<sup>2</sup>  
Connectable conductor cross section solid-core (EF007337)  
0.2 mm<sup>2</sup>  
Type of electric connection (EF003961)  
Spring clamp connection  
Connectable cable type (EF006816)  
Tubular cable  
Material of contact surface (EF004020)  
Tin  
Material contact (EF007544)  
Copper  
Material insulation body (EF007543)  
Polyamide (PA)  
Housing material (EF001596)  
Other  
Housing colour (EF000136)  
Black  
Inflammability class of insulation material according to UL94 (EF002521)  
V0  
Operating temperature (EF002393)  
-40 °C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFMC 1,5/15-STF-3,5 BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.