

INDUSTRIAL COMPONENT DATA

DFMC 1,5/ 3-ST-3,5 BD:42-46 1013955 PHOENIX CONTACT

Connector for printed circuit board, number of poles: 3,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFMC 1,5/ 3-ST-3,5 BD:42-46



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFMC 1,5/ 3-ST-3,5 BD:42-46
Catalog number	1013955
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-5928A88B72
Generated	2026-08-06

Product Overview

Connector for printed circuit board, number of poles: 3, pitch: 3.5 mm, connection type: spring clamp push-in, color: green, surface contacts: Tin

Connector for printed circuit board, nominal section: 1.5 mm², color: green, rated current: 8 A, dimensioning voltage (III/2): 160 V, surface contacts: Tin, contact type: Connection female, Number of potentials: 6, Number of rows: 2, Number of poles per row: 3, number of connections: 6, article family: DFMC 1.5/. -ST, pitch: 3.5 mm, connection type: Push-in spring connection, connection direction conductor/printed circuit board: 0 °, Stecksystem: MINI COMBICON - DFMC 1.5, Lock: sin, packing type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Circuit board connector, nominal current: 8 A, rated operating voltage (III/2): 160 V, number of poles: 3, pitch: 3.5 mm, connection: spring-clamp Connection Push-in, color: green, surface of contact: Tin

Commercial data

The code for the order One million thirteen thousand nine hundred fifty five

Pieces/pack. 50 PCS

Sales key AAAEAF -

The amount of minimum order 50 PCS

GTIN Four trillion fifty five billion six hundred twenty six million four hundred ninety four thousand two hundred twenty seven

Weight per piece (package included) 3,400 g

Number customs tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Size

Length [l] 23,35 mm

Width [w] 11,3 mm

Height [h] 13.25 mm

Step 3.5 mm

Measure 7 mm

General

Family article DFMC 1,5/-ST

N. of poles Three

Link Spring-clamp connection Push-in

Nominal section 1.5 mm²

Indications for lug

Proper crimping tool recommended 1212034 CRIMPFOX 6

Crimp connector without the collar insulator, in accordance with DIN 46228-1 Section: 0.25 mm²; Length: 7 mm

Section: 0.34 mm²; Length: 7 mm

Section: 0.5 mm²; Length: 8 mm ... 10 mm

Section: 0.75 mm²; Length: 8 mm ... 10 mm

Section: 1 mm²; Length: 8 mm ... 10 mm

Section: 1.5 mm²; Length: 10 mm

Environmental Product Compliance

China RoHS Period for proper use: unlimited = EFUP-and

Any hazardous substances above the threshold values

Rankings

eCl@ss

eCl@ss 5.1 Twenty seven million two hundred sixty thousand seven hundred

eCl@ss 6.0 Twenty seven million two hundred sixty thousand

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFMC 1,5/ 3-ST-3,5 BD:42-46 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.