

INDUSTRIAL COMPONENT DATA

FKCT 2,5/ 4-ST YE CP24BD:-40SO 1704914 PHOENIX CONTACT Plug-in part, rated current: 12 A, number of poles: 4..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKCT 2,5/ 4-ST YE CP24BD:-40SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKCT 2,5/ 4-ST YE CP24BD:-40SO
Catalog number	1704914
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-1DC7B6EA9A
Generated	2026-08-05

Product Overview

Plug-in part, rated current: 12 A, number of poles: 4, pitch: 5 mm, connection type: Push-in spring connection, color: yellow, contact surface: Tin

Connector for printed circuit board, nominal section: 2.5 mm², color: yellow, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, article family: FKCT 2.5/.. -ST, pitch: 5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Plug component, nominal current: 12 A, number of positions: 4, pitch: 5 mm, connection method: Push-in spring connection, color: yellow, contact surface: Tin

Your advantages

Time saving push-in connection, tools not requiredIntuitive use through colour coded actuation leverQuick and convenient testing using integrated test optionCan be combined with the MSTB 2',5 rangeKey Commercial Data

Orderkey 1704914

Packing unit 1

GTIN 4046356744492

Custom tariff number 85366990

General

Range of articles FKCT 2,5/..-ST

Type of contact Female connector

Number of positions 4

Connection method Push-in spring connection

Rated voltage (III/3) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKCT 2,5/ 4-ST YE CP24BD:-40SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.