

INDUSTRIAL COMPONENT DATA

FOC-PP-SB-LC:6 1411901 PHOENIX CONTACT Splice box

Brand: PHOENIX CONTACT | Manufacturer Part Number: FOC-PP-SB-LC:6



Manufacturer	PHOENIX CONTACT
MPN / Reference	FOC-PP-SB-LC:6
Catalog number	1411901
Category	Network hub
Minimum order	1 Pcs
Document ID	EO-B9BF0CA03E
Generated	2026-08-02

Product Overview

Splice box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1411901

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 385 (C-2-2017)

GTIN 4046356944953

Weight per Piece (excluding packing) 757.700 g

Custom tariff number 85367000

Country of origin DE (Germany)

Mechanical characteristics

Number of slots 6

Connection profile LC connectors

Fiber type GOF

Ferrule diameter 1.25 mm

Insertion/withdrawal cycles > 500

Connection method LC duplex

Type of contact Fiber optics connectors

Cable outlet above and below

Type of cable For all common cable types

Color light grey RAL 7035

Mounting type DIN rail mounting

Degree of protection IP20

Type Rail-mountable module

No. of cable outlets 2

Type of note Order information:

Note DIN rail splice box, including pigtails, splice comb and preassembled completely ready to splice, is available under Order No. 1420318

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C (IEC 61300-2-22)

Ambient temperature (assembly) -5 °C ... 55 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Degree of protection IP20

Material data

Flammability rating according to UL 94 V0

Housing material Sheet steel

Housing surface material Powder-coated, gray

Housing width 52 mm

Depth 110 mm

Height 150 mm

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.119030100eCl@ss 6.01...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FOC-PP-SB-LC:6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.