

INDUSTRIAL COMPONENT DATA

NS 35/15 ZN PERF 2000MM 1206599 PHOENIX CONTACT DIN rail perforated

Brand: PHOENIX CONTACT | Manufacturer Part Number: NS 35/15 ZN PERF 2000MM



Manufacturer	PHOENIX CONTACT
MPN / Reference	NS 35/15 ZN PERF 2000MM
Catalog number	1206599
Category	Mounting rail
Minimum order	50 Pcs
Document ID	EO-AA19DB5E5E
Generated	2026-08-03

Product Overview

DIN rail perforated

Symmetrical perforated rail, similar EN 60715, material:Steel, galvanized, Standard profile, color:silver, Packaging variant with 25 units (50 m)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 1206599

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 577 (C-3-2017)

GTIN 4017918173050

Weight per Piece (excluding packing) 1,320.000 g

Custom tariff number 72166190

Country of origin DE (Germany)

Dimensions

Height 15 mm

Length 2000 mm

Width 35 mm

Hole width 15.00 mm

Hole height 6.20 mm

Drill hole spacing 25.00 mm

General

Material Steel

Coating galvanized

Color silver

Standards and Regulations

Test standard similar to EN 60715

Connection in acc. with standard IEC / EN

Classifications

eCl@ss 4.027110804eCl@ss 4.127110804eCl@ss 5.027141143eCl@ss 5.127141100eCl@ss 6.027400600eCl@ss
7.027400602eCl@ss 8.027400602eCl@ss 9.027400602

ETIM 2.0EC001285ETIM 3.0EC001285ETIM 4.0EC000212ETIM 5.0EC000212ETIM 6.0EC001285

UNSPSC 6.0130212109UNSPSC 7.090139121708UNSPSC 1139121708UNSPSC 12.0139121708UNSPSC
13.239121708

ETIM for 1206599 Power distribution systems (EC001285)

Feature Name

Feature Value

Material (EF002169)

Steel

Surface protection (EF000139)

Other

Punch shape (EF001457)

Long-slot

Drill hole distance centrically (EF002677)

25 mm

Material thickness (EF000386)

1.5 mm

Length (EF001438)

2000 mm

Height (EF000040)

15 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NS 35/15 ZN PERF 2000MM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.