

INDUSTRIAL COMPONENT DATA

EMG 45-DIO 8M-1N5408 2954882 PHOENIX CONTACT Diode block

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMG 45-DIO 8M-1N5408



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMG 45-DIO 8M-1N5408
Catalog number	2954882
Category	Surge protection module
Minimum order	1 Pcs
Document ID	EO-239AB801C1
Generated	2026-08-02

Product Overview

Diode block
Diode module, with 8 diodes, common anode, diode type 1N 5408

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Relays**

Additional Product Information

Technical dataProduct propertiesProduct type Diode module
Data management status
Article revision 04
Insulation characteristics
Pollution degree 2
Input dataDiode
Description of the input 8 diodes, common anode
Diode type 1 N 5408
Max. operating voltage U_{max} 250 V AC
Peak reverse voltage per diode 1000 V
Reverse current per diode 10 μ A
Conducting state voltage per diode approx. 0.8 V
Conducting state current per diode 1.5 A (with single load)
0.3 A (with simultaneous loads)

Connection dataConnection method Screw connection
Stripping length 8 mm
Screw thread M3
Conductor cross section rigid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
DimensionsWidth 45 mm
Height 75 mm
Depth 55 mm
Material specificationsColor green (RAL 6021)
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -40 °C ... 70 °C
ApprovalsCE
Certificate CE-compliant
Note and EN 61326
Standards and regulationsStandards/regulations DIN EN 50178
MountingMounting type DIN rail mounting
Assembly note in rows with zero spacing
Mounting position any
ETIM for 2954882 Low-voltage industrial controls and switchgear (EC000683)
Feature Name
Feature Value
Function (EF000030)
Other
Voltage type (operating voltage) (EF005294)
AC/DC
Operating voltage AC 50 Hz (EF008206)
250 V
Operating voltage AC 60 Hz (EF008207)
250 V
Operating voltage DC (EF008208)
250 V
With LED indicat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMG 45-DIO 8M-1N5408 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.