

INDUSTRIAL COMPONENT DATA**EMG 90-DIO 32M 2954934 PHOENIX CONTACT Diode block**

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMG 90-DIO 32M



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMG 90-DIO 32M
Catalog number	2954934
Category	Surge protection module
Minimum order	1 Pcs
Document ID	EO-E635818CD4
Generated	2026-08-02

Product Overview

Diode block

Diode module, with 32 diodes, common anode, diode type 1N 4007

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **PHOENIX CONTACT > Industrial Relays****Additional Product Information**

Technical dataProduct propertiesProduct type Diode module

Data management status

Article revision 07

Insulation characteristics

Pollution degree 2

Input dataDiode

Description of the input 32 diodes, common anodes

Diode type 1 N 4007

Max. operating voltage U_{max} 250 V AC

Peak reverse voltage per diode 1300 V

Reverse current per diode 5 µA

Conducting state voltage per diode approx. 0.8 V

Conducting state current per diode 0.7 A (with single load)

0.2 A (with simultaneous loads)

Connection dataConnection method Screw connection

Stripping length 8 mm
Screw thread M3
Conductor cross section rigid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
DimensionsWidth 90 mm
Height 75 mm
Depth 55 mm
Material specificationsColor green (RAL 6021)
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -40 °C ... 70 °C
ApprovalsCE
Certificate CE-compliant
Note and EN 61326
Standards and regulationsStandards/regulations DIN EN 50178
MountingMounting type DIN rail mounting
Assembly note in rows with zero spacing
Mounting position any
ETIM for 2954934 Low-voltage industrial controls and switchgear (EC000683)
Feature Name
Feature Value
Function (EF000030)
Other
Voltage type (operating voltage) (EF005294)
AC
Operating voltage AC 50 Hz (EF008206)
250 V
Operating voltage AC 60 Hz (EF008207)
250 V
With LED indication (EF005950)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMG 90-DIO 32M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.