


INDUSTRIAL COMPONENT DATA

ZEC 1,5/ 4-ST-5,0 C2 R1,4 1883064 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZEC 1,5/ 4-ST-5,0 C2 R1,4



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZEC 1,5/ 4-ST-5,0 C2 R1,4
Catalog number	1883064
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-5E97350DF5
Generated	2026-08-04

Product Overview

Printed-circuit board connector

Direct connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 10 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: ZEC 1.5/.. -ST, pitch: 5mm, connection type: Spring connection, mounting: Direct plug-in connection technique, driver/printed circuit board connection direction: 0°, plug-in system: ZEC, locking: Snap-in lock, fixing type: Snap flange, packing type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1883064

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 365 (C-1-2013)

GTIN 4017918161026

Weight per Piece (excluding packing) 6.480 g

Custom tariff number 85366930

Country of origin GR (Greece)

Dimensions

Length [l] 24.05 mm

Width [w] 21.4 mm

Height [h] 17.5 mm

Pitch 5 mm

Dimension a 15 mm

General

Range of articles ZEC 1,5/...-ST

Number of positions 4

Connection method Spring-cage connection

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 10 A

Nominal cross section 1.5 mm²

Maximum load current 10 A (with 1.5 mm² conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 7 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²

Conductor cross section AWG min. 24

Conductor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZEC 1,5/ 4-ST-5,0 C2 R1,4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.