

INDUSTRIAL COMPONENT DATA

UT 4-TG-EX 3046143 PHOENIX CONTACT Disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-TG-EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-TG-EX
Catalog number	3046143
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-8F45CAED01
Generated	2026-08-04

Product Overview

Disconnect terminal block

Interruptible terminal, Current and voltage are determined by the connector used., nominal voltage: 500 V, nominal current: 20 A, connection type: Screw connection, Dimensioning section: 4 mm², section: 0.14 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3046143

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 233 (C-1-2017)

GTIN 4046356919180

Weight per Piece (excluding packing) 13.240 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note Current and voltage are determined by the plug used.

Number of levels 1

Number of connections 2
Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Machine building
Plant engineering
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current I_N 20 A
Maximum load current 20 A (with 6 mm² conductor cross section)
20 A (with 6 mm² conductor cross section)
Nominal voltage U_N 500 V
Open side panel No
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg
Fire protection for rail vehicles (DI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-TG-EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.