


INDUSTRIAL COMPONENT DATA

UT 4-HEDI-P/P 3046252 PHOENIX CONTACT Lever-type disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-HEDI-P/P



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-HEDI-P/P
Catalog number	3046252
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-4513608032
Generated	2026-08-03

Product Overview

Lever-type disconnect terminal block

Lever-interruptible terminal block, with threaded sockets for test plugs to accommodate test pins, nominal voltage: 500 V, nominal current: 20 A, connection type: Screw connection, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, color: black/orange

Lever-type disconnect terminal block, With test socket screws for insertion of test plugs, nom. voltage: 500 V, nominal current: 20 A, connection method: Screw connection, Rated cross section: 4 mm², cross section: 0.14 mm² - 6 mm², mounting: NS 35/7,5, NS 35/15, color: black/orange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Disconnect terminal block

Area of application Railway industry

Machine building

Plant engineering

Number of connections 2

Number of rows 1

Potentials 1

Data management status

Article revision 16

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Rated surge voltage 6 kV

Maximum power dissipation for nominal condition 1.02 W

Maximum current with single arrangement 20 A

Connection data Number of connections per level 2

Nominal cross section 4 mm²

Screw thread M3

Tightening torque 0.6 ... 0.8 Nm

Stripping length 9 mm

Internal cylindrical gage A4

Connection in acc. with standard IEC 60947-7-1

Conductor cross section rigid 0.14 mm² ... 6 mm²

Cross section AWG 26 ... 10 (converted acc. to IEC)

Conductor cross section flexible 0.14 mm² ... 6 mm²

Conductor cross section, flexible [AWG] 26 ... 10 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 4 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 4 mm²

2 conductors with same cross section, solid 0.14 mm² ... 1.5 mm²

2 conductors with same cross section, flexible 0.14 mm² ... 1.5 mm²

2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.14 mm² ... 1.5 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 2.5 mm²

Nominal current 20 A

Maximum load current 20 A (with 6 mm² conductor cros...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-HEDI-P/P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.