


**INDUSTRIAL COMPONENT DATA**

# UT 4-PE/HEDI 3074004 PHOENIX CONTACT Lever-type disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-PE/HEDI



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | PHOENIX CONTACT       |
| MPN / Reference | UT 4-PE/HEDI          |
| Catalog number  | 3074004               |
| Category        | Ground terminal block |
| Minimum order   | 50 Pcs                |
| Document ID     | EO-B9DFEEC29E         |
| Generated       | 2026-08-01            |

## Product Overview

Lever-type disconnect terminal block

Lever-interruptible terminal block, nominal voltage: 500 V, nominal current: 20 A, connection type: Screw connection, Sizing cross-section: 2.5 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting: NS 35/7.5, NS 35/15, color: black/orange

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

Key Commercial Data

Orderkey 3074004

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 231 (C-1-2017)

GTIN 4046356416245

Weight per Piece (excluding packing) 24.990 g

Custom tariff number 85365080

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm<sup>2</sup>  
Color black/orange  
Insulating material PA  
Flammability rating according to UL 94 V0  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation for nominal condition 1.02 W  
Maximum load current 20 A (with 6 mm<sup>2</sup> conductor cross section)  
Nominal current I<sub>N</sub> 20 A  
Nominal voltage U<sub>N</sub> 500 V  
Open side panel No  
Dimensions  
Width 6.2 mm  
Length 70.8 mm  
Height NS 35/7,5 73 mm  
Height NS 35/15 80.5 mm  
Connection data  
Note Please observe the current carrying capacity of the DIN rails.  
Connection method Screw connection  
Screw thread M3  
Stripping length 9 mm  
Tightening torque, min 0.6 Nm  
Tightening torque max 0.8 Nm  
Connection in acc. with standard IEC 60947-7-1/IEC 60947-7-2  
Conductor cross section solid min. 0.14 mm<sup>2</sup>  
Conductor cross section solid max. 6 mm<sup>2</sup>  
Conductor cross section AWG min. 26  
Conductor cross section AWG max. 10  
Conductor cross section flexible min. 0.14 mm<sup>2</sup>  
Conductor cross section flexible max. 6 mm<sup>2</sup>  
Min. AWG conductor cross section, flexible 26  
Max. AWG conductor cross section, flexible 10  
Conductor cross section flexible, with ferrule without plastic sleeve...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-PE/HEDI with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.