


INDUSTRIAL COMPONENT DATA

UTT 4-TG P/P 3044801 PHOENIX CONTACT Disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTT 4-TG P/P



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTT 4-TG P/P
Catalog number	3044801
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-2EB3BAE693
Generated	2026-08-01

Product Overview

Disconnect terminal block

Interruptible terminal, The current and voltage are determined by the connector used., with threaded females for test sockets to house test pins, nominal voltage: 500 V, nominal current: 30 A, connection type: Screw connection, Dimensioning section: 4 mm², section: 0.14 mm² - 6 mm², Separation zone, mounting: NS 35/7.5, NS 35/15, Color: Gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3044801

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 59 (CL-2009)

GTIN 4017918997137

Weight per Piece (excluding packing) 20.890 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 2

Number of connections 4

Potentials 1

Nominal cross section 4 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)

Maximum load current 38 A (with 6 mm² conductor cross section)

Nominal current IN 30 A

Nominal voltage UN 500 V

Maximum load current 20 A (with 6 mm² conductor cross section)

Nominal current IN 20 A

Nominal voltage UN 500 V

Open side panel Yes

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 M...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTTB 4-TG P/P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.